

15K-2P Spec Sheet



Solar Inp	Input Power 19,500W	
Max Allowed PV Power	19,500W	
Max PV Power Delivered to Battery &	15,000W	
Max DC Voltage (Voc)	500V @ 26A	
MPPT Voltage Range	125-425V	
Starting Voltage	125V	
Number of MPPT	3	
Max Solar Strings Per MPPT	2	
Max DC Current per MPPT (Self Lim-	26A	
Max AC Coupled Input (Micro/String	19,200W	

AC Output Power 15kW On-Grid & Off-Grid		
Connections	120/240/208V Split Phase	
Continuous AC Power to Grid (On-Grid)	15,000W 62.5A-L (240V)	
Continuous AC Power to Load (Off-	12,000W 50A-L (240V)	
Surge AC Power 10sec	24,000VA L-L (240V)	
Surge AC Power 100ms	30,000VA L-L (240V)	
Parallel Stacking	Yes - Up to 12	
Frequency	60/50Hz	
Continuous AC Power with Grid or Generator	48,000W 200A L-L (240V)	
CEC Efficiency	96.5% (Peak 97.5%)	
Idle Consumption Typical—No Load	90W	
Sell Back Power Modes	Limited to Household/Fully	
Design (DC to AC)	Transformerless DC	
Response Time (Grid-Tied to Off-Grid)	5ms	
Power Factor	+/- 0.9 - 1.0	

Battery (optional) Output Power 12,000W	
Туре	Lead-Acid or Li-lon
Nominal DC Input	48V
Capacity	50 — 9900Ah
Voltage Range	43.0 — 63.0V
Continuous Battery Charging Output	275A
Charging Curve	3-Stage w/ Equalization
Grid to Batt Charging Efficiency	96.0%
External Temperature Sensor	Included
Current Shunt for Accurate % SOC	Integrated
External Gen Start Based on Voltage	Integrated
Communication to Lithium Battery	CanBus & RS485

General	
Dimensions (H x W x D)	31.8" x 18.3" x 10.9"
Weight (package)	135 lbs
Enclosure	IP65 / NEMA 3R
Ambient Temperature	-40~60°C, >45°C Derating
Installation Style	Wall-Mounted
Wi-Fi & LAN Communication	Included
Standard Warranty (verified by HALT Testing)	10 Years

Protections & Certifications	
Electronics Certified Safety by SGS Labs to NEC & UL Specs - NEC 690.4B & NEC 705.4/6	Yes
Grid Sell Back — UL1741-2010/2018, IEE- E1547a-2003/2014, FCC 15 Class B, UL1741SB,	Yes
PV DC Disconnect Switch — NEC 240.15	Integrated
Ground Fault Detection — NEC 690.5	Integrated
PV Rapid Shutdown Control — NEC 690.12	Integrated
PV Arc Fault Detection — NEC 690.11	Integrated
PV Input Lightning Protection	Integrated
PV String Input Reverse Polarity Protection	Integrated
AC Output Breakers - 200A	Integrated
200A x 2 Battery Breaker / Disconnect	Integrated
Surge Protection	DC Type II / AC Type II